Uniden

ADV10 Series UHF CB Transceiver

For more exciting new products please visit our website Australia: www.uniden.com.au

OWNER'S MANUAL

Charging Rechargeable Batteries



Do not charge alkaline or non rechargeable batteries.

Plug the Micro-USB charge cable into the radio's charge port (single radio charging) or to the Dual Drop-in cradle, and the USB end to a standard USB charge port, or USB port of an AC adaptor (not included). Plug the AC adaptor into the wall outlet

- Before operating the radio, charge the rechargeable batteries for 16 hours without interruption
- Do not transmit when the radio is charging.

The changing battery icon on the display indicates the battery is charging.







Low Battery Alert

If the battery level becomes low, the unit will go into a Battery Low Mode. The Transmit Mode is disabled. Replace Alkaline batteries immediately, or recharge NiMH rechargeable batteries immediately to continue using the radio.

Power Save

Your ADV10 Series has a unique circuit designed to dramatically extend the life of the batteries. If there is no transmission nor an incoming call within 5 seconds, your Radio switches to the Power Save mode. The Radio is still able to receive transmis sions in this mode

CTCSS and DCS Codes - 'Silent PIN' When you don't want to hear chatter from other users on a channel, who are not part of your group, you can set a 'Silent PIN' (CTCSS or DCS code). The silent pin works to keep your radio silent, unless someone is transmitting using the same silent pin - so only share your pin setting with those in your group. The ADV10 has 104 pins (codes) available (01~104).

The radios in your group must be set to the same 'Silent PIN' (CTCSS or DCS code). When communicating with other ADV series radios you just select the same pin code. You can set a different pin code for each channel using this procedure.

- Set a desired channel to use a 'Silent PIN' on (Ex. CH 01). 2. Press MENU two times. The PIN (code) number flashes
- 3. Press **UP** or **DOWN** to select a setting; - PIN 00 Setting is disabled (Off) - PINs 01~38 (CTCSS codes 01~38)
- PINs 39~104 (DCS codes 39~104).

Ex. 1 shows Channel 01 with Silent PIN 38 (CTCSS code #38)



8

4. Press PTT to save the code setting.

NOTE: Set to 00 to disable the feature for the current channel

Ex. 2 shows Channel 01with Silent PIN 104 (DCS code #104)

If you are communicating with non ADV series radios then let them know the code type (CTCSS or DCS) and number your are

OPERATION

Turning Your Radio On and Off Press and hold o to turn the radio On or Off.

CONTROLS & INDICATORS

Included in your Package

 3 AA Rechargeable Batteries* Micro-USB charge cable[^]

Dual Drop-in Charge Cradle^

88:55

ADV10 Series Radio*

 Operating Guide[^] *Per radio, ^One only

Antenna -

Push To Talk

(PTT)

Call Tone /

Monitor On/Off

Flashlight

/ Key Lock

[▼] Down

Speaker

Belt Clip*

When turning on, the radio chirps and the display briefly shows all the display icons before showing the current standby mode of your



2CH SCAN HI VOX III

-LED Flashlight

Menu / Power On/Off

- Scan / VOX On/Off

Microphone

Micro-USB

Charging Jack

1

Display

- [▲] Up

The ADV10 has an automatic display back light which remains on for 5 seconds after a key press (all keys except PTT key). The back light will work even if the keypad is locked but will not work during low battery alert mode.

Setting the Volume

Press the **UP** button to increase the speaker volume Press the **DOWN** button to decrease the speaker volume

The speaker volume setting is indicated by 'L'.

The volume level range is from 1 (minimum) to 7 (maximum). Volume level 0 is mute, indicated by ■x

Ex. lowest volume H





LED Flashlight (LAMP)

To use the built-in LED flashlight;

1. Press **LAMP** to turn the LED flashlight On or Off.

NOTE: The lamp function will work when radio power is Off. 5

Scanning Channels

Use scanning to monitor channels for transmissions or to find someone in your group who has accidentally changed channels

4

- 1. Press and release SCAN. The SCAN indicator displays. 2. Press and release **SCAN** again to disable scanning.
- The **SCAN** indicator disappears.

When the radio detects channel activity, it stops scanning and you can hear the transmission. To respond to the transmission, press PTT within 5 seconds,the channel will be confirmed.

Scan Advance

If the radio stops scanning on a channel you do not want to listen to, briefly press and release ${\bf UP}$ or ${\bf DOWN}$ to temporarily remove that channel from scan and resume scanning. Removed chanels are restored when the radio is powered off then on again.

Setting and Transmitting Call Tones

Your radio can transmit different call tones (wake-up tone) to other radios in your group so you can alert them that you want to talk. To set a call tone:

- 1. Press the MENU three times. 'CA' appears on the display. The current call tone setting flashes.

 2. Press UP or DOWN to change and hear the next call tone.
- There are 20 call tones to choose from (1-20). NOTE: Set the call tone to 0 to disable the call tone feature.
- 3. Press PTT to set the new call tone Press CALL to transmit the call tone

NOTE: Current regulations require calling tones to be restricted to one transmission per minute. If a second transmission is attempted within one minute then an error tone will sound. 9

MENU List

Open the MENU - Press MENU Step through MENU - Press MENU again Exit the MENU - Press PTT

Channel Number

HI Transmit Power is Hi

2CH Dual Channel is On

SCAN Scan is on

VOX VOX is on

Installing Batteries

GETTING STARTED

Install the 3 AA Alkaline batteries

inside of the battery compartment

I ift the battery

cover latch up.

1. With the back of the radio facing you, locate the latch to release the battery cover and remove the cover.

2. Install 3 AA NiMH rechargeable batteries as shown on the

'Silent PIN'

Battery Level

■ Volume Mute

Key Lock is on

(CTCSS or DCS Code)

2

6

for current Channel

Transmit Receive Icon

Insert 3 AA NiMH

Belt Clip

To remove:

Radio Battery Meter

Talking and Listening

3. Replace the battery cover and press down to secure

Pinch and hold belt clip latch and slide the belt clip up.

- Charge only at room temperatures.

Slide the belt clip down into the catch until it snaps into place.

Battery bars indicate the battery level . When the battery

meter shows 1 bar, the device goes into low battery mode and indicates low battery in the form of an alert tone.

- Charge only at rount temperatures.
- Only charge NiMH rechargeable batteries.
- Do not mix and use old/new/alkaline/NiMH batteries.

- Batteries may corrode over time and cause permanent damage to your devices.

To communicate, all radios in your group must be set to the same Channel (and the same 'Silent PIN' Code if it is set).

Hold the radio 5 to 7 cm away from your mouth when speaking.

For maximum range and extended the life of the batteries, $\ensuremath{\text{avoid}}$ touching the antenna with your

To talk, press and hold PTT. • Indicates transmission.

When you are finished speaking, release PTT to listen.

Checking the Channel Before Transmitting

hear static, the channel is clear to use

you press PTT for 60 continuous seconds.

Operation With the Aid of a Repeater

Eg. CH01 is being used in your area for repeater use

Push to Talk Timeout Timer

For uninterrupted communication, do not talk on a channel if

If a 'Silent PIN' (CTCSS or DCS code) is enabled, check for

To prevent accidental transmissions and save battery life, the

NOTE: You can only activate Duplex on Channels 01-08 and

41-48. When Duplex is ON for a repeater channel, the display

shows r1-r8 for Channels 01-08 and n1-n8 for Channels 41-48

Press **MENU** seven times. 'r P' setting flashes. Press **UP** or **DOWN** to change the change the setting ON or OFF.

radio emits a continuous warning tone and stops transmitting if

someone else is currently talking on it. 🗼 Indicates a signal is

activity on a channel before you talk, press and hold MON. If you

The transmit power is 1.0 Watt or 0.5 Watt.

hand when transmitting.

- Remove the batteries from the radio for storage.

- Charge rechargeable NiMH batteries once every 3 months when not in use.

Close the battery

cover firmly

One	CHANNEL setting
Two	CTCSS Code setting
Three	Call Tone setting
Four	VOX setting
Five	Dual Watch (2nd Channel) setting
Six	Transmit Power Level (Hi / Low)
Seven	Duplex Mode (Repeater) setting

Setting a Channel

The ADV10 uses the UHF-CB channels (CH01-CH80). See UHF CHANNELS & FREQUENCIES, page 12 for channel usage

- Press MENU one time. The current channel flashes. 2. Press UP or DOWN button to select a desired channel.
- 3. Press PTT to confirm and save the channel setting.
- Setting the Transmit Power

The ADV10 can be set to 1 Watt (HI) or 0.5 Watt (LO) transmit

power. **HI** displays when the level is high.

1. Press **MENU** six times. The current level flashes

- Press **UP** or **DOWN** button to select a desired channel
- 3. Press PTT to confirm and save the transmit power setting.
- Automatic SQUELCH

The ADV10 is equipped with an automatic squelch, which mutes the speaker audio unless a strong enough signal is present. As this is automatic, there is no user input required to adjust it.

Voice Operated Transmission (VOX)

Transmission is initiated by speaking into the microphone of the radio instead of pushing the PTT button.

Press VOX to turn VOX On or Off. VOX appears on the display

The VOX sensitivity level can be changed in the Menu.

- 1. Press MENU four times. VOX icon will display
- The current setting (1-3) will flash. 2. Press UP and DOWN button to select the sensitivity level
- 3. Press PTT to set the new setting.
- - 1 = Low Sensitivity (for quieter areas) 2 = Medium Sensitivity 3 = High Sensitivity (for noisy areas)

Dual (Channel) Watch

You can monitor a second channel along with the current channel with this setting.

- 1. Press MENU five times. 'CH' appears on the display The second channel to monitor will flash. (OF, 01 - 80) If the setting is OF, then Dual Watch is disabled. 2. Press UP or DOWN to set the 2nd channel to monitor.
- 3. Press PTT to save the setting and dual watch will be enabled
- The second channel will be monitored intermittently To Operate in Duplex Mode (Repeater Mode)

The Duplex function enables you to access local repeater

stations. UHF CB Repeaters are used to retransmit or relay your signal. Repeaters will extend the range of your radio and overcome the shielding effect caused by solid obstructions 10

Key Beep ON/OFF

Press and hold the **DOWN** button while turning the radio ON to switch the keypad tone ON or OFF.

To lock the key pad:
Press and hold • until the key lock indicator appears.

Press and hold • until the key lock indicator disppears.

Press PTT to save

Key Lock ON/OFF

2. To unlock the key pad:

Roger Beep ON/OFF Roger Beep is a unique tone added to end a transmission

Press and hold the **UP** button while turning the radio ON to turn

Roger Beep ON or OFF. 11

Statement of Remedy: If the Product is found not to conform to this warrant as stated above, the Warrantor, at its discretion, will either repair the defect or replace the Product without any charge for parts or service. This warranty does not include any reimbursement or payment of any consequential damages

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

claimed to arise from a Product's failure to comply with the warranty.

This warranty is in addition to and sits alongside your rights under either the COMPETITION AND CONSUMER ACT 2010 (Australia) or the CONSUMER GUARANTEES ACT (New Zealand) as the case may be, none of which can be

Procedure for obtaining warranty service: Depending on the country in which the Product was first purchased, if you believe that your Product does not conform with this warranty, you should deliver the Product, together with satisfactory evidence of your original purchase (such as a legible copy of the sales docket) to Uniden at the address shown below. You should contact Uniden regarding any compensation that may be payable for your expenses incurred in making a warranty claim. Prior to delivery, we recommend that you make a backup copy of any phone numbers, images or other data stored on your Product, in case it is lost or damaged during warranty service.

UNIDEN AUSTRALIA PTY LTD

UHF CHANNELS & FREQUENCIES



- Please follow these guidelines for channel use in Australia:

 Channels 05 and 35 are Emergency Channels.

 Channel 11 is a Calling Channel.

 Channels 22 and 23 are for telemetry and telecommand applications, channels 61, 62 and 63 are for future use and TX is inhibited on these channels.

- General communication is accepted on all other channels with these guidelines:

 Channel 40 road channel (Australia).

 Channels 01-08 (and 31-38), and Channels 41-48

(and 71-78) are repeater channels Important information - 80 Channel UHF-CB channel expansion

To provide all users additional channel capacity within the UHF-CB Band. The ACMA will change the majority of the current wideband channel use to narrowband channel use. This allows for additional channels to be added, up to 80 Channels. This simply means that the new narrowband radio you have purchased will have more channels than older radios. Please refer to the guidelines above and the channel chart for further channel information.

A list of currently authorised channels can also be obtained from the ACMA website in Australia and the MBIE website in New Zealand. Interference / Poor Audio

When a new narrowband radio receives a signal from an older wideband radio the speech may sound loud. Narrowband radios operating on CH41 - CH80 may encounte interference from a nearby wideband radios transmitting on high power on an adjacent channel (frequency).

When an older wideband radio receives a signal from a new narrowband radio the speech may sound quiet - the wideband radio user simply adjusts their radio volume for best performance. The above situations are not a fault of the radio but a symptom of mixed older wideband radios are phased out this issue will be eliminated

User License Information USER LICENSE INFORMATION



The citizen band radio service is licenced in Australia by ACMA Radio-communications (Citizen Band Radio Stations) Class Licence and in New Zealand by MBIE General User Licence for Citizen Band Radio and operation is subject to conditions

Splashproof Information



SPLASHPROOF LEVEL (IPX4)
This ADV10 radio, when covers and seals are fully closed, can withstand water splashes to IPX4 level rating. Always ensure the radio is fully dry before charging in the Dual



Uniden does not represent this product to be waterproof. Do not expose this product to immersion in water

WATER WARNING

13

WARRANTY

UNIDEN ADV10 Series UHF CB Transceiver

IMPORTANT: Satisfactory evidence of the original purchase is required Please refer to our Uniden website for any details or warranty durations offered in

addition to those contained below. Warrantor: The warrantor is Uniden Australia Pty Limited ABN 58 001 865 498

Terms of Warranty: Uniden Aust warrants to the original retail purchaser only that the ADV10 Series ("the Product"), will be free from defects in materials and craftsmanship for the duration of the warranty period, subject to the limitations and

Warranty period: This warranty to the original retail purchaser is only valid in the original country of purchase for a Product first purchased either in Australia or New Zealand and will expire one (1) year from the date of the original retail sale.

If a warranty claim is made, this warranty will not apply if the Product is found by (A) Damaged or not maintained in a reasonable manner or as recommended

- in the relevant Uniden Owner's Manual; Modified, altered or used as part of any conversion kits, subassemblies or
- any configurations not sold by Uniden Improperly installed contrary to instructions contained in the relevant Owner's Manual
- Repaired by someone other than an authorized Uniden Repair Agent in relation to a defect or malfunction covered by this warranty; or
- (E) Used in conjunction with any equipment, parts or a system not manufactured by Uniden

Parts Covered: This warranty covers the Product and included accessories

User-generated Data: This warranty does not cover any claimed loss of or damage to user-generated data (including but without limitation phone number addresses and images) that may be stored on your Product.

