



GEAR FOR LIFE

SEAT COVER INSTALLATION INSTRUCTIONS

CONGRATULATIONS ON YOUR PURCHASE

of your new Premium Canvas Seat Covers! When installed correctly, MSA 4X4 seat covers will not move and will provide long lasting comfort and protection for your vehicle's seats. To ensure you get a perfect fit, our seat covers are made extremely neat & tight. This means the fitting time may take a little longer.

Driver & passenger seats marked on the underside of seat cover (199)

TOYOTA LANDCRUISER 76 SERIES SECOND ROW FULL WIDTH BENCH MODEL NO: LC770

1. Remove Headrest.
2. Place top section of cover over the top of the seat and pull down firmly.
3. Push flap through between upper and lower seat towards rear.
4. Close side Velcro flaps.
5. From rear pull flap through firmly and attach Velcro.
6. Reinstall headrest.
7. Place seat cover over base of seat, ensuring cutouts are positioned correctly over front hinges and side levers.
8. Push all rear straps through between upper and lower seat towards rear.
9. From rear, pull the cover firmly into position.
10. Tilt seat forward and attach all front to back side release buckles.
11. Attach long side to side side release buckle.
12. Attach two rear side to back side release buckles.
13. Tension all straps.
14. Ensure seat cover is a neat fit all round and adjust if necessary.