

WATERSNAKE®

GEO-SPOT 65LB

12V GPS BOW MOUNT MOTORS

GPS TECH INCLUDING ANCHOR MODE

Anchor Mode, Pilot Mode, Cruise Mode and Navigation Mode.

EFFICIENT 65LB THRUST ON 12V

Plenty of power for trailer boats up to 750kg loaded weight.

WIRELESS HANDHELD REMOTE

Stay in control, anywhere on your boat.

LiFePO4 BATTERY COMPATIBLE

Use a lightweight 12V LiFePO4 lithium battery up to 14.5V in use.



- ANDERSON PLUGS FOR EASY CONNECTIONS
- BUILT-IN VOLTAGE PROTECTION UP TO 14.5V
- STAINLESS STEEL PROPELLER SHAFT

- READY FOR SALTWATER: TOUGH COMPOSITE SHAFT, SACRIFICIAL ZINC ANODE, ENCAPSULATED DRIVER MODULE.
- STRONG REINFORCED-NYLON THREE-BLADE WEEDLESS PROPELLER

VOLTAGE	12V
MOUNTING TYPE	Bow mount XB bracket
STEERING CONTROL	Wireless handheld remote & GPS
SPEEDS	Efficient digital variable
SHAFT MATERIAL	Composite
SHAFT DIAMETER	1.2 inches (30mm) Ø

COLOUR	White
VOLTAGE PROTECTION	Built-in protection up to 14.5V. No circuit breaker or fuse needed.
REQUIRED BATTERY	12V deep cycle or LiFePO4 Lithium up to 14.5V in use.
GPS CAPABILITY	Yes
FOOT CONTROL COMPATIBILITY	Yes



GEO-SPOT 65LB - MODEL COMPARISON

More Geo-Spot 65lb info at watersnake.com.au

CODE	BARCODE	MODEL	MAX. THRUST	SHAFT LENGTH	AMP DRAW	MAX. MOTOR POWER OUT	MAX RPM (NO LOAD)	MOTOR WEIGHT	3-BLADE PROPELLER	SUGGESTED BATTERY CAPACITY
55313	9312327870442	Geo-Spot SW65/54	65lb	54"	0-43A	350W	1650rpm	15kg	94mm pitch	100 Ah or larger
55316	9312327871449	Geo-Spot SW65/60	65lb	60"	0-43A	350W	1650rpm	15kg	94mm pitch	100 Ah or larger
55314	9312327872415	Geo-Spot SW65/66	65lb	66"	0-43A	350W	1650rpm	15kg	94mm pitch	100 Ah or larger

OPTIONAL ACCESSORIES SOLD SEPARATELY



WATERSNAKE GEN 3 FOOT CONTROLLER



WATERSNAKE GEO-SPOT GPS NAV SENSOR



WATERSNAKE NYLON QUICK RELEASE BRACKET



WATERSNAKE NYLON QUICK RELEASE PUCK PLATE