

- DIGITAL VOLTAGE METER
- ANDERSON PLUGS FOR EASY CONNECTIONS
- STAINLESS STEEL PROPELLER SHAFT
- THREE-BLADE WEEDLESS PROPELLER

VOLTAGE	12V
STEERING CONTROL	Wireless handheld remote
SPEEDS	Efficient digital variable
SHAFT MATERIAL	Composite
SHAFT DIAMETER	1.2 inches (30mm)

SHAFT WALL THICKNESS	4.25mm				
VOLTAGE PROTECTION	Built-in protection up to 14.5V. No circuit breaker or fuse needed.				
REQUIRED BATTERY	12V deep cycle or LiFePO4 Lithium up to 14.5V in use.				
GPS CAPABILITY	No				
FOOT CONTROL COMPATIBILITY	No				

FIERCE 2 - MODEL COMPARISON

More Fierce 2 info at watersnake.com.au

CODE	BARCODE	MODEL	MAX THRUST	SHAFT LENGTH	AMP DRAW	MAX. MOTOR POWER OUT		MOTOR WEIGHT	WEEDLESS PROPELLER	SUGGESTED BATTERY CAPACITY
55276	9312327875393	Fierce 2 54 / 48	54lb	48"	0-50A	290W	1700rpm	12.2kg	94mm pitch	100 Ah or larger
55277	9312327875409	Fierce 2 65 / 54	65lb	54"	0-43A	350W	1650rpm	12.6kg	Reinforced nylon 94mm pitch	100 Ah or larger

OPTIONAL ACCESSORIES SOLD SEPARATELY



WATERSNAKE NYLON QUICK RELEASE PUCK PLATE KIT



WATERSNAKE NYLON QUICK RELEASE BRACKET



WATERSNAKE ALLOY QUICK RELEASE BRACKET